


MAGELY S LOUNGE



LOUNGE Version - 12,2 m / 12,8 m Coach - Cursor 9 Diesel EURO VI



Layout 12.2 m 53 seats +1+1+ WC
Seats 28 to 55* with or w/o wheelchair area



Layout 12.8 m 53 seats +1+1+ WC+ UFR
Seats 28 to 59* with or w/o wheelchair area

*Maximum passengers capacity (depends on permitted weights according to local legislation)

Length	12200 mm	12765 mm
Width	2550 mm	
Height	3620 mm	
Wheelbase	6321 mm	6886 mm
Front / Rear Overhang	2619 / 3260 mm	
Front / Rear Tread (steel rim)	2014 / 1817 mm	
Inner / Floor height	2100 / 1380 mm	
Wall-to-wall turning radius	10771 mm	11493 mm
Kerb-to-kerb turning radius	8982 mm	9704 mm
Approach / Departure angles	7°/7°	
GVW (max legally permitted weight depends on local legislation)	18000 / 19000 kg	
Max. Front axle load	7100 kg	
Max. Rear axle load technically admitted	12600 kg	
Volume of inner luggage racks	1.25 m ³	1.31 m ³
Volume luggage w/o driver berth	9.5 m ³	10.8 m ³
Volume luggage with driver berth	7.5 m ³	8.8 m ³

CURSOR 9 EURO VI

Power @ 1600 rpm	294 kW (400 hp)
Torque	1700 Nm @1250 rpm
Displacement	8,7 litres
6 cylinders in line, vertical transverse at the rear, Common Rail	

IVECO BUS

MAGELYS - LOUNGE Version - 12,2 m / 12,8 m Coach - Cursor 9 Diesel EURO VI

BODY AND EXTERIOR EQUIPMENT

- Roof panel in sheet metals; front and rear face in polyester
- Anti-corrosion treatment by cathaphoretic immersion
- Front and middle door with one wing outwards opening
- Rear view mirrors with electric defrosting and adjustment and wide angle mirrors

INTERIOR EQUIPMENT

- High end leather passenger seats
- Front and middle steps moulded of plastic with anti-slip coverings
- Removable carpet on the entrance steps, driver platform & aisle
- Separation moulded
- Pleated curtains
- Side panels trimming and Luggage rack lining
- Digital clock / temperature display
- Refrigerator integrated in the dashboard (75cans of 33cl)

AUDIO/VIDEO

- Professional Line 3 radio
- 2 motorized LCD 19" 16/9 video screens
- Hostess microphone

ELECTRICAL EQUIPMENT

- Accumulators batteries 230 A/h
- Alternators 140A + 140A
- Protection by circuit breakers
- Halogen lighting
- Front fog lights, with cornering light function
- LED D.R.L., sidemarkers, rear lighting block
- LED lighting of driver area and door accesses
- Passenger compartment lighting with LED continuous lighting
- 12 V Plug / 24 V Plug

WINDOWS/ THERMAL COMFORT

- Tinted side windows (double glazing) as well as rear window
- 2 glazed venting openings in the roof
- Fully integrated HVAC with 4 evaporators units
- 30kW independent heating programmable
- Central roof windows

DRIVER EQUIPMENT

- Driver seat with adjustable inclination of the backrest, microphone and heating
- Driver's seat armrest
- Driver's side console
- Electrical defrosting driver's window
- Driver front electric sun-visor & side manual sun-visors
- Hostess seat & compartment in the luggage rack
- Board computer (controlled from the steering wheel)

- Side panels in sheet aluminum and polyester
- Luggage compartment doors at pantograph

Optional:

- Painting and adhesive customization

- Coffee machine / Drinks dispenser

Optional:

- Vacuum cleaner integrated
- Water or chemical toilet with flush system
- "Luxury" or basic removable carpet

Optional:

- Charger for 6 CD / DVD
- 3 motorized LCD 19" 16/9 video screens
- Tuner for TV reception

- Ethylometer
- Interface FMS(fleet management system)
- Central locking with remote control

Optional:

- Xenon lighting
- Emergency signal in connection with door opening

- Convector heating
- Driver's window with electric defrosting

Optional:

- Without central roof windows

- GPS navigation
- Digital tachograph
- Cameras : Hostess / Road / Middle door
- Reversing camera

Optional:

- Driver berth

ENGINE

- IVECO CURSOR 9 with Hi-SCR after treatment system
 - Diesel Oxydation Catalyst and Diesel Particulate Filter
 - Selective Catalytic Reduction of NOx with urea
 - Clean Up Catalyst
- Double cartridge fuel filter. Fuel pre-filter with water separator
- Large capacity air filter with blockage warning

GEARBOX

- Gearbox robotized ZF 12 AS 2001 with Eco Switch
- Exterior warning buzzer with the shift of reverse speed
- Reversing sensor /

REAR AXLE

- Rear axle U17X MERITOR (MICHELIN tyres)
 - Standard axle ratio 4,11
- (*) with speed limiter at 100 km/h due to European legislation

Engine Ratio (ZF)	CURSOR 9 (400 Hp)	
	ZF 6S 1911	ZF 12AS 2001
4.11	129 km/h*	n/a
3.70	143 km/h*	143 km/h*
3.36	157 km/h*	157 km/h*

FRONT AXLE/ STEERING

- Independent wheel front axle
- Worm-type steering ZF type 8098 with integrated power steering

SUSPENSION

- Fully pneumatic with set up control
- In the front: 2 bellows / 2 shock absorbers / 1 anti-roll bar
- In the rear: 4 bellows / 4 shock absorbers / 4 retaining drawbars / 1 anti-roll bar

COMPRESSED AIR

- Dual cylinder air compressor 630 cm3 "ENERGY SAVING"
- Air dryer & oil capture
- Manual bleeding valves on the air tanks, inflation taps

SAFETY

- AEBS / LDWS
- ESP, EBS, ABS. with ASR
- Service brakes with pneumatic control, disk brakes in the front&rear
- Parking brake: 2 spring cylinders

FUEL TANK AND UREA TANK

- 420 l diesel tank
- 80 l urea tanks

TYRES AND WHEELS

- Tyres 295/80 R22.5

Optional

- Front / rear equipment to increase/decrease the suspension height

Optional

- ACC

Optional

- 420 l + 60 l Webesto
- 480 l / 640 l diesel tank

Optional

- Aluminum rims